


WC-SYSTEM FOR DRY-WALL CONSTRUCTION VICONNECT

PRODUCT INFORMATION

1 . POSITION



Model	922475
Collection	ViConnect
PROJECTS	 PLUS
Width	525 mm
Height	820 mm
Depth	155 mm
Weight	13,85 kg
description	<p>for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, Easy connection to flush plate via flexible cables with bayonet joint, depth adjustment front edge of element: 135-205 mm incl. 2 wall mounts, incl. self-locking feet with adjustable base plates and fastening materials, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate tested in accordance with DIN EN 14055 packaged in a box</p> <p>For combination with: for wall-mounted WC self-supporting powder-coated steel frame, fully pre-assembled, front/top operated, with small inspection opening</p> <p>Please order flush plate separately. concealed cistern with insulation against condensation with dual flush, maximal flush quantity 4/7,5 l, factory setting 6/3 l, filling valve Noise Class I, corner valve R1/2, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, certification marks for concealed cistern: Noise Class I</p> <p>for dry-wall construction, low</p>

Specification texts

ViConnect; Toilet installation system; Size: 525 x 820 x 155 mm; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, Easy connection to flush plate via flexible cables with bayonet joint, depth adjustment front edge of element: 135-205 mm; incl. 2 wall mounts, incl. self-locking feet with adjustable base plates and fastening materials, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate; tested in accordance with DIN EN 14055; packaged in a box; For combination with: for wall-mounted WC; self-supporting powder-coated steel frame, fully pre-assembled, front/top operated, with small inspection opening; Please order flush plate separately.; concealed cistern with insulation against condensation with dual flush, maximal flush quantity 4/7,5 l, factory setting 6/3 l, filling valve Noise Class I, corner valve R1/2, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, certification marks for concealed cistern: Noise Class I; for dry-wall construction, low

COLOURS

92247500 4051202338015

TECHNICAL DRAWINGS

922475

